

# mark Levinson<sup>®</sup>

by HARMAN



**Luxury Audio**

Pristite SE – November 2020




Bülow  
steensen

## Source Players




Model	Product Description	Part #		Detail Pris inkl.moms
<b>Nº519</b> 	<p>The Mark Levinson Nº 519 is a complete, modern music player for today's music lover. It combines wireless and wired music streaming with a traditional CD player, plus connections for USB drives, additional digital sources, Roon certified, MQA support and Bluetooth audio and HARMAN Clari-Fi® technology; all in an uncompromising package featuring Mark Levinson proprietary system design and a 6000-series aluminum chassis.</p> <p>The Nº 519 sports a large, color display, comes with a matching remote control, and also can be controlled with iOS and Android apps, all major web browsers, and a host of system integration connections. Like all Mark Levinson products, the Nº 519 is proudly designed and handcrafted in the USA</p> <ul style="list-style-type: none"> <li>• Digital inputs: 1 balanced; 2 coaxial; 2 optical; 1 USB asynchronous, Bluetooth receiver</li> <li>• Mass storage: 2 USB type A</li> <li>• Network: Ethernet, Wi-Fi 802.11b/g/n</li> <li>• PCM input sample rates; 32, 44.1, 48, 88.2, 96, 176.4, and 192kHz</li> <li>• PCM input bit depth: up to 32</li> <li>• DSD: native, single (2.8MHz) and double-speed (5.6MHz)</li> <li>• Main analog outputs: 1 pair balanced; 1 pair single-ended</li> <li>• Headphone output: 1 1/4-inch (6.3mm)</li> <li>• Digital outputs: 1 balanced; 1 coaxial; 1 optical</li> <li>• Control I/O: Ethernet, RS-232, Trigger In and Out, IR In</li> <li>• Software update: Network, USB</li> <li>• Power requirements: 100, 115, or 230V AC, factory set for destination country</li> <li>• Control apps: iOS, Android, web browser</li> </ul>	NO519EU		249.995 SEK
<b>Nº5101</b> 	<p>The Mark Levinson Nº 5101 is a complete, modern music player for today's music lover. It combines wireless and wired music streaming with a traditional CD/SACD player, plus connections for USB drives, additional digital sources,</p> <ul style="list-style-type: none"> <li>• Digital inputs: 1 coaxial; 1 optical; 1 USB asynchronous, Bluetooth receiver</li> <li>• Mass storage: 2 USB type A</li> <li>• Network: Ethernet, Wi-Fi 802.11b/g/n</li> <li>• PCM input sample rates; 32, 44.1, 48, 88.2, 96, 176.4, and 192kHz</li> <li>• DSD: native, single (2.8MHz) and double-speed (5.6MHz)</li> <li>• Main analog outputs: 1 pair balanced; 1 pair single-ended</li> <li>• Digital outputs: 1 coaxial; 1 optical</li> <li>• Control I/O: Ethernet, RS-232, Trigger In and Out, IR In</li> <li>• Software update: Network, USB</li> <li>• Power requirements: 100, 115, or 230V AC, factory set for destination country</li> <li>• Control apps: Music Life</li> </ul>	MLN05101EU		65.995 SEK

<p><b>Nº515</b></p> 	<p>Turntable</p> <ul style="list-style-type: none"> <li>• First-class analog source designed for the Pure Phono stage found in the No523. No526 and No585.5</li> <li>• Highly-dampened composite and aluminum sandwich main chassis</li> <li>• Custom gimbal-mounted, 3D printed tonearm with integral headshell for smooth and fluid tracking</li> <li>• Integrated electronic speed control for precision 33 and 45 RPM performance at the touch of a button</li> <li>• Optimized drive system with mechanically isolated enclosure and triple belt drive</li> <li>• High-torque AC synchronous motor</li> <li>• Uncompromised chassis construction with exceptional dampening properties</li> <li>• Machined Delrin and Aluminum feet with a vibration-dampening polymer core</li> <li>• Solid Aluminum platter rotates on an inverted bearing</li> <li>• Stainless steel shaft spinning in a phosphor bronze bushing for maximum rotational accuracy</li> <li>• Precision-machined pulley and triple belt drive system provides smooth, quiet operation</li> <li>• Included Ortofon moving coil phono cartridge (MLNO515MCEU only)</li> </ul>	<p>MLNO515EU MLNO515MCEU</p>		<p>139.995 SEK 159.995 SEK</p>
<p><b>Nº5105</b></p> 	<p>Turntable</p> <ul style="list-style-type: none"> <li>• Custom 10" tonearm</li> <li>• Isolation mounted 12v Synchronius Motor</li> <li>• Integrated electronic speed control for precision 33 and 45 RPM performance at the touch of a button</li> <li>• Massive solid brushed aluminium plinth precision machined from a single billet</li> <li>• 14lb Solid Aluminum platter</li> <li>• Included Ortofon moving coil phono cartridge (MLNO5105MC only)</li> </ul>	<p>MLNO5105 MLNO5105MC</p>		<p>76.995 SEK 88.995 SEK</p>




## Power Amplifiers

Model	Product Description	Part #		Detail Pris inkl.moms
<b>Nº536</b> 	<p>Monaural Amplifier</p> <ul style="list-style-type: none"> <li>• Input connectors: one XLR Balanced, one RCA Unbalanced</li> <li>• Speaker connectors: two pairs of Hurricane loudspeaker outputs with banana-plug sockets (except on 230 VAC version)</li> <li>• Control connectors: Ethernet, RS-232, Trigger In, Trigger Out, USB-A, Mini USB</li> <li>• Rated output power: 400W RMS @ 8 ohms, 800W RMS @ 4 ohms, 20Hz to 20kHz at &lt;0.3% THD, full output from 2.83VRMS</li> <li>• Frequency response: 10Hz to 20kHz +/- 0.2dB</li> <li>• Signal-to-noise ratio: &gt;85dB, reference level 2.83 VRMS</li> <li>• Input impedance: 60 k<math>\Omega</math> balanced; 30 k<math>\Omega</math> unbalanced</li> <li>• Voltage gain: 26dB</li> <li>• Input sensitivity: 2.83 VRMS output at 142mVRMS input</li> <li>• Power requirements: 100V~, 120V~, 230V~; factory set for destination country, 1500W</li> <li>• Dimensions (H x W x D): 7.65" x 17.75" x 19.83" (119.4 cm x 45.1 cm x 50.4 cm)</li> <li>• Weight: Net weight 100 lbs (45.4kg); Shipping weight: 117 lbs (53kg)</li> </ul>	NO536EU		189.995 SEK
<b>Nº534</b> 	<p>Dual-Monaural Amplifier</p> <ul style="list-style-type: none"> <li>• Input connectors: one pair Balanced, one pair single-ended</li> <li>• Speaker Connectors: four pairs of Hurricane loudspeaker outputs, banana-plug sockets per channel, except on European versions</li> <li>• Control I/O: Ethernet, RS-232, Trigger In and Out, USB-A, Mini USB</li> <li>• Rated Output Power: 250 wpc RMS @ 8<math>\Omega</math>, 20Hz to 20kHz @ &lt;0.3% THD, full output from 2.83VRMS</li> <li>• Frequency Response: 10Hz to 20kHz <math>\pm</math>0.2dB</li> <li>• Signal-to-Noise Ratio: &gt;85dB, reference level: 2.83 VRMS</li> <li>• Input Impedance: 60 k<math>\Omega</math> balanced; 30 k<math>\Omega</math> unbalanced</li> <li>• Voltage Gain: 26dB</li> <li>• Input Sensitivity: 2.83VRMS output at 142mVRMS input</li> <li>• Power Requirements: 100V~, 120V~, 230V~, factory set for destination country, 1500W</li> <li>• Dimensions (H x W x D): (with feet): 7.75" (19.7cm) / (without feet): 7" x 17.75" x 20" (19.7cm/17.8cm x 45.1cm x 50.8cm)</li> <li>• Weight: Net weight: 107 lbs (48.5kg); Shipping weight: 124 lbs (56.3kg)</li> </ul>	NO534EU		249.995 SEK
<b>Nº5302</b> 	<p>Dual-Monaural Amplifier</p> <ul style="list-style-type: none"> <li>• Input connectors: one pair Balanced, one pair single-ended</li> <li>• Bridgeable – 550watt in 4ohm</li> <li>• Control I/O: Ethernet, RS-232, Trigger In and Out, USB-A, Mini USB</li> <li>• Rated Output Power: 135 wpc RMS @ 8<math>\Omega</math>, 20Hz to 20kHz @ &lt;0.3% THD, full output from 2.83VRMS</li> <li>• Rated Output Power: 270 wpc RMS @ 4<math>\Omega</math>, 20Hz to 20kHz @ &lt;0.3% THD, full output from 2.83VRMS</li> </ul>	MLNO5302EU		121.995 SEK

## Preamplifiers

Model	Product Description	Part #		Detail Pris inkl.moms
<b>Nº526</b> 	Dual-Monaural Pure Path Preamplifier with Precision Link DAC and Pure Phono <ul style="list-style-type: none"> <li>• Analog Inputs: 2 balanced (XLR), 3 single-ended (RCA) line, 1 single-ended (RCA) phono w/ ground</li> <li>• Digital Inputs: 1 balanced (XLR); 2 coaxial (RCA); 2 optical (Toslink); 1 USB-B asynchronous</li> <li>• Analog Outputs: 1 balanced (XLR); 1 pair single-ended (RCA), 1 headphone (¼", 6.3mm TS)</li> <li>• Output Impedance: &lt;80Ω single ended, &lt;160Ω balanced</li> <li>• Dimensions (H x W x D): Height (with feet): 3.75" / Height (without feet): 3.25" x 17.25" x 18" (10.2cm / 8.9cm x 43.8 cm x 45.7 cm)</li> <li>• Weight: Net weight: 41 lbs (17.7kg)</li> </ul>	NO526EU		249.995 SEK
<b>Nº523</b> 	Dual-monaural Preamplifier <ul style="list-style-type: none"> <li>• Analog Inputs: 2 balanced (XLR), 3 single-ended (RCA) line, 1 single-ended (RCA) phono w/ ground</li> <li>• Analog Outputs: 1 balanced (XLR); 1 pair single-ended (RCA), 1 headphone (¼", 6.3mm TS)</li> <li>• Output Impedance: &lt;80Ω single ended, &lt;160Ω balanced</li> <li>• Dimensions (H x W x D): Height (with feet): 3.75" / Height (without feet): 3.25" x 17.25" x 18" (10.2cm/8.9cm x 43.8cm x 45.7cm)</li> <li>• Weight: Net weight: 39 lbs (17.7kg)</li> </ul>	NO523EU		189.995 SEK
<b>Nº5206</b> 	Dual-Monaural Pure Path Preamplifier with Precision Link DAC and Pure Phono <ul style="list-style-type: none"> <li>• Analog Inputs: 2 balanced (XLR), 2 single-ended (RCA) line, 1 single-ended (RCA) phono w/ ground</li> <li>• Digital Inputs: 1 balanced (XLR); 2 coaxial (RCA); 2 optical (Toslink); 1 USB-B asynchronous</li> <li>• Analog Outputs: 1 balanced (XLR); 1 pair single-ended (RCA), 1 headphone (¼", 6.3mm TS)</li> </ul>	MLNO5206EU		121.995 SEK

## Integrated Amplifiers

Model	Product Description	Part #		Detail Pris inkl.moms
<b>Nº5802</b> 	Integrated Amplifier <ul style="list-style-type: none"> <li>• 125Wpc into 8 ohms   250Wpc into 4 ohms</li> <li>• Analog audio inputs: None</li> <li>• Digital audio inputs: One USB, one AES/EBU, two coaxial, two optical, Bluetooth aptX</li> <li>• Analog audio outputs: One RCA stereo pair (variable)</li> <li>• Headphone output: One ¼-inch jack (front panel)</li> <li>• Communication and control: Ethernet, USB, RS-232, IR input, and 12V trigger input and output</li> </ul>	MLNO5802EU		92.995 SEK
<b>Nº5805</b> 	Integrated Amplifier with Phono Stage <ul style="list-style-type: none"> <li>• 125Wpc into 8 ohms   250Wpc into 4 ohms</li> <li>• Analog audio inputs: One XLR and two RCA stereo pairs</li> <li>• Phono inputs: One RCA stereo pair MC and one RCA stereo pair MM plus ground terminal</li> <li>• Digital audio inputs: One USB, one coaxial, two optical, Bluetooth aptX</li> <li>• Analog audio outputs: One RCA stereo pair (variable)</li> <li>• Headphone output: One ¼-inch jack (front panel)</li> <li>• Communication and control: Ethernet, USB, RS-232, IR input, and 12V trigger input and output</li> </ul>	MLNO5805EU		106.995 SEK
<b>Nº585.5</b> 	Stereo integrated amplifier (200 Watts x 2) + Pure Phono input for MM and MC cartridges + Improved remote commander design <ul style="list-style-type: none"> <li>• 32-bit/192kHz D/A convertor with asynchronous USB input</li> <li>• Patented Clari-Fi™ signal processing for compressed audio formats</li> <li>• Analog pre-outs with selectable 80Hz crossover filter for 2.1-channel capability</li> <li>• Fully-differential, Class AB amplifier rated at 200W into 8 ohms and stable into 2 ohms</li> <li>• Analog audio inputs: One XLR and three RCA stereo pairs</li> <li>• Digital audio inputs: One USB, one AES/EBU, two coaxial and two optical</li> <li>• Analog audio outputs: One RCA stereo pair with selectable 80Hz crossover</li> <li>• Communication and control: Ethernet, USB, RS-232, IR input, and 12V trigger input and output</li> <li>• Dimensions: 7.6" x 17.1" x 19.9" (193mm x 434mm x 506mm)</li> <li>• Weight: 74 lb (34kg)</li> </ul>	NO585.5EU		189.995 SEK

Bülow  
STEENSEN

